SP	SPECIFICATION FOR TURFING		
1.	Cut turf to an even depth of 50mm, lay on protective covering to avoid further		
	damage to existing grassed areas.		
2.	Rer	nove top soil to the required depth and store separately.	
<u> </u>			
3.	Rer	nove subsoil to required depth and store separately.	
4	Def		
4.	Before turfing and before final cultivation supply and apply, at the manufacturers recommended rates, a Longlife Preseeder N.P.K. 8:12:8Mg, or		
	an agreed equivalent.		
5.	a)	After fertilising carry out further cultivation to reduce top 25mm to a fine	
		tilth.	
	b)	Rake to a true, even lightly firmed surface, removing all stoners more than	
		50mm in any dimension.	
6.	Provide suitable turf to BS3969 to match existing from local supplier to be		
	agreed by Fife Council.		
7.	Turf to be laid to the following specification:		
	a)	Lay turf with broken joints, well butted up, working from planks laid on	
	,	previously laid turves.	
	b)	Use whole turves at edges, trim to true line.	
	<u>c)</u>	Adjust levels by raking out or infilling with fine soil under turves.	
	d)	Consolidate by lightly and evenly firming with wooden beaters as the laying proceeds. DO NOT USE ROLLERS .	
	e)	Dress turf with lightly sifted top soil/peat/sand and brush well to	
	0)	completely fill joints.	
	f)	Thoroughly water the completed turf within 24 hours if there is no rain.	
	g)	Allowances must be made for settlement to ensure final levels match	
		surrounding levels.	
	h)	All work to be carried out by an approved contractor.	
8.	Upa	n completion of the reinstatement works a standard 12 month liability	
		od will apply.	

CON	IDITIONS (TURFING)	
9.	The contractor must carry out the work when soil and weather conditions are suitable for the relevant operations, i.e. do not lay turves when persistent cold or drying winds are likely to occur or soil is frost bound, waterlogged or excessively dry.	
10.	The contractor will be responsible for the newly turfed area until successful establishment. This will include protection, irrigation and cutting allowing no growth higher than 50mm and no less than 25mm.	
11.	The contractor will be responsible for bare areas of dead grass which become apparent. Any such areas will be regarded as defects due to materials or workmanship and must be made good by re-cultivation and returfing.	
12.	Use only machinery and tools suitable for the site conditions and the work to be carried out.	
13.	The contractor will be responsible for reinstating any damage to surrounding area subsequent upon the works.	
14.	The contractor shall ensure that all cut turf is to be replaced within a 3 day working period.	
The	following British Standards are to be observed:	
Top	Soil – B.S.3882	
Turf: B.S.3969		
i uii.	2.0.0000	